

# AL Pro系列



# 行家首选 桌上型打印机



可节省标签需求的方案!



## 使用前



花費大量的時間和金錢，卻只能用到前一代的低階桌上型條碼機。

## 使用后



使用新一代的桌上型条码机，有效节省时间和人力。

## 应用范围



**零售业**



**制造业**



**货运物流业**

## 丰富的功能让每日工作简单又轻松



### 全新贝壳式设计，易于安装

AL Pro系列采用全新贝壳式设计，不仅易于开关盖，安装纸卷与碳带也更加方便。

**speed-up**

### 列印速度升级到每秒7英寸

最高速度可以达到每秒7英寸，即使在最高速列印的状态，依然保有完美的列印品质。



### 无缝转移到Argox印表机!

自动侦测和切换指令集  
自动采用常见印表机控制指令集，使用上更友善(自动侦测和自动转换)

\*展示影片请洽销售人员



### 多样化连接界面

内建网口，两个USB hosts，USB device，RS-232串口，并且可选配Wi-Fi、Bluetooth无线网络。

规格	AL-4210 Pro	AL-4310 Pro
列印方式	热敏式 & 热转印	
分辨率	203 dpi (8 dots/mm)	300 dpi (12 dots/mm)
最快打印速度	7寸(每秒)	6寸(每秒)
最大打印长度	100"(2540 mm)	50"(1270 mm)
最大列印宽度	4.25"(108 mm)	4.16"(105.7 mm)
内存	128MB SDRAM, 128MB Flash ROM USB储存最大可至32GB	
CPU类型	32 位元 RISC 微处理器	
<b>耗材规格</b>		
感测器	纸张反射式感测器(可调整)/纸张穿透式感测器(固定, 6.27mm偏移)	
纸张种类	纸卷式、标签式(间距纸、连续纸、折叠纸、票券、吊牌...等)	
纸张载体	最大宽度: 4.65"(118mm) 最小宽度: 0.8"(20mm) 纸张厚度: 0.0024"~0.008" (0.06mm~0.2mm) 纸卷轴心1"/1.5"(25.4/38mm)可容纸卷外径5"(127mm) 纸卷轴心0.5"(127mm)可容纸卷外径4.5"(115mm) 经销商选配外挂纸架: 纸卷外径(OD):8",纸卷轴心:1"/3"	
碳带规格	宽度: 1"~4.33"(25.4mm~38mm) 最大长度: 110m 轴心内径: 0.5"(12.7mm) 轴心宽度: 4.33"(110mm)(开缺口) 适用种类: 蜡质、半蜡半树脂、全树脂(内卷式和外卷式碳带皆适用)	
<b>字体与条码</b>		
字体	五种国际标准字型(1.25mm~6mm), 最大可达 24x24, 四方向旋转0° ~ 270° 支援GB18030简中字体,可下载Windows True Type仿真字型	
一维条码	PPLA: Code 39, UPC-A, UPC-E, Code 128 subset A/B/C, EAN-13, EAN-8, HBIC, Codabar, Plessey, UPC2, UPC5, Code 93, Postnet, UCC/EAN-128, UCC/EAN-128 K-MART, UCC/EAN-128 Random weight, Telepen, FIM, Interleaved 2 of 5 (Standard/with modulo 10 checksum/ with human readable check digit/ with modulo 10 checksum & shipping bearer bars), GS1 Data bar (RSS) PPLB: Code 39, UPC-A, UPC-E, Matrix 2 of 5, UPC-Interleaved 2 of 5, Code 39 with check sum digit, Code 93, EAN-13, EAN-8 (Standard, 2 /5digit add-on), Codabar, Postnet, Code128 subset A/B/C, Code 128 UCC (shipping container code), Code 128 auto, UCC/EAN code 128 (GS1-128), Interleave 2 of 5, Interleaved 2 of 5 with check sum, Interleaved 2 of 5 with human readable check digit, German Postcode, Matrix 2 of 5, UPC Interleaved 2 of 5, EAN-13 2/5 digit add-on, UPCA 2/5 digit add-on, UPCE 2/5 digit add-on, GS1 Data bar (RSS) PPLZ: Code39, UPC-A, UPC-E, Postnet, Code128 subset A/B/C, Interleave 2 of 5, Interleaved 2 of 5 with check sum, Interleaved 2 of 5 with human readable check digit, Code 93, Code 39 with check sum digit, MSI, EAN-8, Codabar, Code 11, EAN-13, Plessey, GS1 Data bar (RSS), Industrial 2 of 5, Standard 2 of 5, Logmars	
二维条码	MaxiCode, PDF417, Data Matrix (ECC 200 only), QR code, Composite Codes, Aztec	
图片格式	PPLA: PCX, BMP, IMG, HEX,GDI / PPLB: PCX, BMP, Binary raster, GDI / PPLZ: GRF, Hex, GDI	
指令集	PPLA, PPLB, PPLZ, Auto	
<b>介面与配件</b>		
操作介面	LED指示燈 x 2(三種燈色), 按鍵 x 1	
通讯介面	USB device, RS-232, Ethernet, USB host x 2	
驱动程式	Windows Driver for Vista/Win7/Win8/Win10, LINUX Driver, macOS Driver, Raspberry Pi Driver	
工具软体	BarTender, ArgoxBar Pro, Printer Tool, Font Utility, iLabelPrint+	
资料库连结	Argobar Pro support ODBC Database Connection: Excel, CSV, MS Access, MS SQL, Oracle MySQL, dBASE (*.dbf)	
<b>电源与环境</b>		
电源供应	切换式电源供应器, 交流输入100~240V, 50~60Hz 直流输出 24V, 2.5A	
环境条件	操作环境: 41°F~104°F (5°C~40°C). 相对湿度: 0%~90% 储存环境: -4°F~122°F (-20°C~50°C).	
安规认证	CB, CE, FCC, IC, RoHS, UL, CCC	
<b>物理规格</b>		
尺寸	宽 209mm x 高 179.2mm x 深 266mm	
重量	4.8 lbs (2.2 kg)	

\*立象科技保留增加和修改规格的权利, 恕不另行通知。请联络立象科技业务代表以获取最新规格。

### 选购配件



闸刀裁纸器



旋刀裁纸器



剥纸器



无线区域网络



支援蓝牙 v4.2  
支援iOS、安卓  
连线



支援蓝牙 v2.1  
支援安卓连线



外挂纸架



請洽詢當地的合作夥伴  
以了解更多訊息

