



OX-100 Pro 桌上型标签条码打印机



产品简介

OX-100 Pro 条码打印机是Argox精益求精的崭新产品,在外观的设计上更是本产品的最新亮点!流线型的外观,沉稳内敛的尊贵黑,更是您在各类应用的最佳选择,不管是在商场,政府机关,办公室等都为原本的空间带来更高品味的视觉享受!

在高水准的外观下,搭配32位的微处理器可以储存更大容量的文档数据;多样化的接口设计,使条码打印机与主机之前的通讯更加灵活方便!



应用领域



零售业



服装标签



图书馆



畜牧业



汽机车制造业



政府自动化



资产管理



电子半导体业



行政事务



手机通讯业

OX-100 Pro 桌上型标签条码打印机



技术参数	OX-100 Pro
打印方式	热敏/热转印
分辨率	203 dpi
打印速度	2~3 ips
最大打印长度	43英寸 (1092毫米)
最大打印宽度	4.1英寸 (104毫米)
内存	128MB SDRAM (32MB 使用者可用), 128MB Flash ROM (80MB 使用者可用)
CPU	32 位RISC微处理器
标签感测方式	反射式
操作面板	2个LED指示灯, 1个按钮
通讯接口	串口(RS-232)、 USB
字体	五种国际标准字型(1.25mm~6mm), 支援GB18030简中字体, 最大可达 24x24, 四方向旋转0° ~ 270°, 可下载Windows 字形
一维条码	PPLA: Code 39, UPC-A, UPC-E, Code 128 subset A/B/C, EAN-13, EAN-8, HBIC, Codabar, Plessey, UPC2, UPC5, Code 93, Postnet, UCC/EAN-128, UCC/EAN-128 K-MART, UCC/EAN-128 Random weight, Telepen, FIM, Interleaved 2 of 5 (Standard/with modulo 10 checksum / with human readable check digit/ with modulo 10 checksum & shipping bearer bars), and GS1 Data bar (RSS) PPLB: Code 39, UPC-A, UPC-E, Matrix 2 of 5, UPC-Interleaved 2 of 5, Code 39 with check sum digit, Code 93, EAN-13, EAN-8 (Standard, 2 /5digit add-on), Codabar, Postnet, Code128 subset A/B/C, Code 128 UCC (shipping container code) , Code 128 auto, UCC/EAN code 128 (GS1-128), Interleave 2 of 5, Interleaved 2 of 5 with check sum, Interleaved 2 of 5 with human readable check digit, German Postcode, Matrix 2 of 5, UPC Interleaved 2 of 5, EAN-13 2/5 digit add-on, UPCA 2/5 digit add-on, UPCE 2/5 digit add-on, and GS1 Data bar (RSS) PPLZ: Code39, UPC-A, UPC-E, Postnet, Code128 subset A/B/C, Interleave 2 of 5, Interleaved 2 of 5 with check sum, Interleaved 2 of 5 with human readable check digit, Code 93, Code 39 with check sum digit, MSI, EAN-8, Codabar, Code 11, EAN-13, Plessey, GS1 Data bar (RSS), Industrial 2 of 5, Standard 2 of 5, and Logmars
二维条码	PPLA: MaxiCode, PDF417, Data Matrix (ECC 200 only), QR code, and Composite Codes PPLB: MaxiCode, PDF417, Data Matrix (ECC 200 only), QR code, and Composite Codes PPLZ: QR code, PDF417, Data Matrix (ECC 200 only), and MaxiCode Composite Codes
图形	PPLA: PCX, BMP, IMG, HEX and GDI format files PPLB: PCX, BMP, Binary Raster, and GDI PPLZ: GRF, Hex and GDI
指令集	PPLA, PPLB, PPLZ
应用软件	Windows Driver for Windows Vista/Win7/Win8/Win10/Win11, LINUX Driver, macOS Driver, Raspberry Pi Driver
纸张种类	纸卷式、标签式 (间距纸、连续纸、折叠纸、票券、吊牌...等)
纸张规格	最大宽度：110毫米 最小宽度：25.4毫米 纸张厚度：0.0635~0.254毫米 最大外径：109毫米 内径宽度：12.7毫米
碳带规格	适用种类：蜡基、混合基、树脂基 (外碳带) 碳带宽度：25~110毫米 最大外径：37毫米 最大长度：91米 内径宽度：12.7毫米 (需有notch安装凹洞)
重量	2.0公斤
尺寸	长278毫米 x 宽186毫米 x 高165毫米
电源	切换式电源供应器 输入：100~240V~1.8A,50-60Hz, 输出：24VDC,2.5A
安装标准	CE, FCC, RoHS, CCC
操作温度	操作环境：4℃~38℃ (相对湿度10%~90%), 储存环境：-20℃~50℃
可选配件	裁刀、外挂纸架、时钟、专利ArgoKee外接式键盘不需接计算机可脱机操作

*本规格未来如有变更,请依实际出厂为主,不再另行通知。